

ATEX II GD - INERIS15ATEX0001X

Pstat : < 500 mbar

Pstat standard : 100 mbar +/-15% @22°C

Max vacuum : 50 mbar pour / for Pstat 100 mbar

Surface / Area: 5010 cm<sup>2</sup>

Kst : dp/dt < 500 bar/s

Kg : dp/dt < 130 bar/s

Pmax < 12 bar / Pred. max < 1.8 bar



- Inox 304L / stainless steel 1.4306

- Inox 316L / stainless steel 1.4404

- Joint / gasket EPDM Temp: -40...+80° C

- Joint / gasket SILICONE FDA Temp: -60..+200° C

Poids unitaire / Unit weight :4,92 kg

|   |                          |                                 |                    |   |
|---|--------------------------|---------------------------------|--------------------|---|
| B   | Maj plan                 | 25/04/2022                      | AV                 | MJ  |
| Ind.  | Objet de la modification | Date                            | Nom                | Vérif.  |
|  | Matière:                 | Date de création:<br>14/01/2015 | A4<br>Ech.:<br>s/e |  |
| Plan n°: 57VL_D800_Clt  |                          |                                 |                    |   |
| Désignation:<br><b>VIGILEX VL Ø800</b>  |                          |                                 |                    |   |