



ATEX II GD - INERIS15ATEX0001X  
 Pstat : < 500 mbar  
 Pstat standard : 100 mbar +/-15% @22°C  
 Max vacuum : 50 mbar pour / for Pstat 100 mbar  
 Surface / Area: 1220 cm<sup>2</sup>  
 Kst : dp/dt < 500 bar/s  
 Kg : dp/dt < 130 bar/s  
 Pmax < 12 bar / Pred. max < 1.8 bar  
 - Inox 304L / stainless steel 1.4306  
 - Inox 316L / stainless steel 1.4404  
 - Joint / gasket EPDM Temp: -40...+80° C  
 - Joint / gasket SILICONE FDA Temp: -60..+200° C

Poids Unitaire / Unit Weight : 1,526 kg

|   |                          |                                 |     |  |
|---|--------------------------|---------------------------------|-----|--|
| A   | Création                 | 25/03/2022                      | AV  | MJ   |
| Ind.  | Objet de la modification | Date                            | Nom | Vérif.   |
|  | Matière:                 | Date de création:<br>25/03/2022 | A4  | Ech.:<br>s/e  |
| Plan n°: 57VL_027046_Clt  |                          |                                 |     |  |
| Désignation:  |                          |                                 |     |  |
| <b>VIGILEX VL 270x458</b>   |                          |                                 |     |  |